

CR-10



REAR SURROUND SPEAKER WITH ADJUSTABLE SOUNDFIELD MANAGEMENT

Adjust from dipolar sound to bipolar at the flip of a switch to fill the room

CONVERGENT SOURCE MODULE

Tweeter and woofer in proximity act as single source to increase dispersion

TWO DYNAMIC .75" HYPERBOLIC ALUMINUM DOME TWEETERS

For accurate highs, simplified placement and an authentic theater experience

4.5" WOOFER WITH RIBBED ELLIPTICAL SURROUND

Deliver tight and powerful distortion-free low-frequency response

GOLD-PLATED 5-WAY BINDING POSTS

Ensure easy, reliable connection for high-quality sound

ALL ENERGY BRAND COMPONENTS WERE DEVELOPED WITH THESE SONIC PRINCIPLES IN MIND:

- Flat On-Axis Frequency Response with Wide Bandwidth**
 Speakers should reproduce the entire audio range in a uniform manner. By ensuring that no one frequency dominates any other, Energy speakers ensures that every note is the way it was intended to be—and the sound is as natural as possible.
- Wide and Constant Dispersion**
 Sound at all frequencies radiating from the speaker should be in an even pattern, in all directions throughout the room.
- Low Distortion and Resonance**
 No speaker system is totally distortion- or resonance-free, but Energy speakers have achieved a significantly lower distortion level—a clearly audible improvement.

SPECIFICATIONS

Speaker System	Bipole/dipole rear surround, magnetically shielded acoustic suspension
Frequency Response (+/- 3dB)	69Hz - 20kHz
Tweeter	2 x .75" (19mm) hyperbolic aluminum-domes
Woofer	4.5" (114mm) w/Ribbed Elliptical Surround
Crossover Point	2.2kHz
Sensitivity	89dB
Impedance	4 Ohms min./8 Ohms nominal
Power Handling	20-150 W per channel
Dimensions H x W x D	10.6 x 6.9 x 5.7 inches 27 x 17.5 x 14.5 cm
Units/Carton	2
Product Weight (Single)	5.5 lbs / 2.5 kg
Inputs	Gold plated 5-way binding posts
Finish	Black ash cabinet
Included Accessories	Manual

ENERGYSPEAKERS.COM