



ENERGY™

Connoisseur™

The Connoisseur Series



ENERGY-SPEAKERS.COM

Convergent Source Module

The Convergent Source Module (CSM) is the heart of Energy speakers. It provides wide dispersion, low distortion and amazing midrange performance. By bringing the speaker's mid/woofer and tweeter as close together as possible, interference between the drivers is eliminated, resulting in uniform on and off axis performance.

Ribbed Elliptical Surround

The Ribbed Elliptical Surrounds that encircle our products' woofers are unlike any other. By changing the shape of the speaker surround to an ellipse, rather than the traditional "half roll," distortion is reduced dramatically. Benefits include increased excursion and larger piston area for greater efficiency.

- High performance custom components
- High-grade black ash finishes; high gloss black baffles
- Aluminum dome tweeters help you hear details you've never before noticed



CF-70

- 3-way floorstanding, magnetically shielded bass reflex with front-firing port
- 1-inch (25.4mm) hyperbolic aluminum dome tweeter
- 5.5-inch (140mm) midrange w/Ribbed Elliptical Surround
- 2 x 6.5-inch (165mm) woofer w/Ribbed Elliptical Surrounds
- 40.7" h x 8.4" w x 15.6" d, 45.3 lbs.



CF-50

- 2.5-way floorstanding, magnetically shielded bass reflex with front-firing port
- 1-inch (25.4mm) hyperbolic aluminum dome tweeter
- 3 x 5.5-inch (140mm) woofers w/Ribbed Elliptical Surrounds
- 38.6" h x 7.1" w x 14.6" d, 39.3 lbs.



CF-30

- 2.5-way floorstanding, magnetically shielded bass reflex with front-firing port
- 1-inch (25.4mm) hyperbolic aluminum dome tweeter
- 2 x 5.5-inch (140mm) woofer w/Ribbed Elliptical Surrounds
- 36" h x 7.1" w x 12.3" d, 30.8 lbs.



CR-10

- Bipole/dipole rear surround, magnetically shielded acoustic suspension
- 2 x .75-inch (19mm) tweeters w/ hyperbolic aluminum domes
- 4.5-inch (114mm) woofer w/Ribbed Elliptical Surround
- Black ash cabinet
- 10.6" h x 6.9" w x 6.3" d, 5.2w lbs.



CB-20

- 2-way bookshelf, magnetically shielded bass reflex with rear-firing port
- 1-inch (25.4mm) hyperbolic aluminum dome tweeter
- 6.5-inch (165mm) woofer w/Ribbed Elliptical Surround
- 12.2" h x 7.6" w x 9.1" d, 11.3 lbs.



CB-10

- 2-way bookshelf, magnetically shielded bass reflex with rear-firing port
- 1-inch (25.4mm) hyperbolic aluminum dome tweeter
- 5.5-inch (140mm) woofer w/Ribbed Elliptical Surround
- 11.4" h x 7.1" w x 8.5" d, 8.9 lbs.



CB-5

- 2-way bookshelf, magnetically shielded bass reflex with rear-firing port
- .75-inch (19mm) hyperbolic aluminum dome tweeter
- 4.5-inch (114mm) woofer w/Ribbed Elliptical Surround
- 8.7" h x 5.7" w x 7.9" d, 6.6 lbs.
- \$180 pr. (U.S. MSRP)



CC-10

- 2.5-way center, magnetically shielded bass reflex with rear-firing port
- 1-inch (25.4mm) hyperbolic aluminum dome tweeter
- 2 x 5.5-inch (140mm) woofer w/Ribbed Elliptical Surrounds
- 7.1" h x 19.7" w x 9.9" d, 17.4 lbs.



CC-5

- 2.5-way center, magnetically shielded bass reflex with rear-firing port
- .75-inch (19mm) hyperbolic aluminum dome tweeter
- 2 x 4.5-inch (114mm) woofer w/Ribbed Elliptical Surrounds
- 14" h x 5.7" w x 8" d, 10.7 lbs.



ESW-C10

- Bass reflex design with down firing port
- 10-inch (25.4 cm) Injection molded cone with Ribbed Elliptical Surround
- 400 Watts dynamic, 150 Watts continuous
- Black ash cabinet with high gloss black baffle trim
- 17" h x 13" w x 14.8" d, 28 lbs.



ESW-C8

- Bass reflex design with down firing port
- 8-inch (20 cm) Injection molded cone with Ribbed Elliptical Surround
- 240 Watts dynamic, 60 Watts continuous
- Black ash cabinet with high gloss black baffle trim
- 12.7" h x 10.5" w x 12.3" d, 16 lbs.