



Specifications	MX Speaker
Speaker Type	Five ultra compact Omnipolar® home theater speakers
Amplifier Power	10 to 100 Watts RMS/ channel
Impedance	8 Ohms nominal / 4 Ohms minimum
Magnetically Shielded	Yes
Frequency Response	110 Hz - 20 kHz
Sensitivity	87dB
Crossover Point	3.5 Khz
Components	Tweeter: 5/8" (16 mm) pure titanium hybrid Woofer: 2 1/2" (64 mm) high efficiency woofer with aluminum cone
Connectors	Integrated push terminals
Dimensions HxWxD	Inches: 4.04 x 3.2 x 3.54 (height with grille 4.33") Cm: 10.2 x 8.14 x 9.0 (height with grille 10.1)
Weight	1.455 lb / 0.66kg
Finish	High gloss black
Cabinet Material	Ultra rigid polycarbonate enclosure
Grille Material	Magnetic with black cloth
Accessories	Integrated dual key way mount
Optional Stands:	Sanus HTB-7 black and similar universal stands

Offering Minimum eXposure and Maximum eXcitement, the MX home theater system delivers big, immersive audio entertainment from our smallest set of speakers yet.

Whether you want to relax to smooth tunes or host a movie screening, the MX serves up some serious wow factorimmersive sound that won't drown out your décor or intrude upon your everyday lifestyle.

Consisting of five palm-size speakers and a miniature subwoofer cube finished in high-gloss black, the MX is a sophisticated surround sound system that perfectly demonstrates what's possible using all of today's incredible technologies. In fact, its exclusive Omnipolar® technology and extremely high-performance components will blow you away, so hold on tight.

Exclusive Omnipolar® technology benefits:

- Immersive 360° audio entertainment; wherever you go, the sound follows
- · Perfect balance of direct and reflected sound, for accurate, realistic listening
- Placement versatility without sacrificing performance

Specifications	MM-6 Subwoofer
Speaker Type	One single active, dual passive subwoofer
Woofer	6.5-inch (16.5 cm) Black anodized aluminum cone with inverted Ribbed Elliptical Surround
Passive Radiators	2 x 6.5-inch (16.5 cm) Black anodized aluminum cones with inverted Ribbed Elliptical Surround
Amplifier Power	800 Watts
Frequency Response	42Hz-200Hz
Max SPL	104dB @ 42Hz, ground plane, 1M
Recommended Sub Crossover	150Hz-180Hz
Variable Low Pass Filter	50Hz-200Hz, Bypass
Phase Control	0° -360°
Inputs	L + R Line in/Sub in
Power Modes	Off/auto/on
Units/Carton	1
Dimensions H x W x D	8 x 8 x 8 inches 20 x 20 x 20 cm
Product Weight	10.1 lbs (4.6 kg)
Finish	High gloss black

