

Omnican OC-45

- Patented Omniguide technology creates immersive 360-degree sound dispersion
- Perfect for in-ceiling complete home theater application
- Indoor or outdoor installation; weather resistant construction
- Rotatable Omniguide module allows fine-tuning of sound in the listening area
- Low profile design
- Woofers feature patented Ribbed Elliptical Surround for increased output and lower distortion
- Easy installation and set up
- Removable back boxes for ease of installation in tight spaces
- Paintable grille and bezel



| Specifications | |
|---------------------------------------|---|
| DESIGN: | Weather resistant Omnipolar in-ceiling speaker |
| SYSTEM TYPE: | 2-Way |
| RECOMMENDED AMPLIFIER POWER: | 10 to 100 Watts |
| NOMINAL IMPEDANCE: | 8 Ohms |
| MINIMUM IMPEDANCE: | 4 Ohms |
| FREQUENCY RESPONSE (+/- 3DB): | 110 Hz - 20 kHz |
| SENSITIVITY (1W/1M): | 88 dB |
| CROSSOVER POINT: | 2.7 kHz |
| TWEETER: | 1" PTH pure titanium hybrid tweeter |
| WOOFER: | 4.5" titanium deposit polypropylene woofer with patented Ribbed Elliptical Surround |
| HEIGHT: | 6.3" / 16 cm (1.6" / 4 cm visible height when installed) |
| WIDTH: | W - 6.89" / 17.5 cm (back box) W - 8.4" / 21.36 cm (outside baffle) |
| RECOMMENDED HOLE CUT-OUT: | Ø 7.0625 / 18 cm |
| REQUIRED INSTALLATION DEPTH: | 4.46" / 11.3 cm |
| CONNECTORS: | High quality spring loaded |
| PACKAGING QUANTITY: | 1 per box |
| COLORS: | White |
| OTHER UNIQUE FEATURES: | Weather resistant design with UV-rated enclosure. Rotatable Omniguide module |
| OPTIONAL INSTALLATION BRACKET: | ICB-45 |