

Omnican OC-65

- Patented Omniguide technology creates immersive 360-degree sound dispersion
- Perfect for in-ceiling complete home theater application
- Indoor or outdoor installation; weather resistant construction
- Rotatable Omniguide module allows fine-tuning of sound in the listening area
- Low profile design
- Woofers feature patented Ribbed Elliptical Surround for increased output and lower distortion
- Easy installation and set up
- Removable back boxes for ease of installation in tight spaces
- Paintable grille and bezel



Specifications	
DESIGN:	Weather resistant Omnipolar in-ceiling speaker
SYSTEM TYPE:	2-Way
RECOMMENDED AMPLIFIER POWER:	10 to 150 Watts
NOMINAL IMPEDANCE:	8 Ohms
MINIMUM IMPEDANCE:	4 Ohms
FREQUENCY RESPONSE (+/- 3DB):	65 Hz - 20 kHz
SENSITIVITY (1W/1M):	90 dB
CROSSOVER POINT:	2.5 kHz
TWEETER:	1" PTH pure titanium hybrid tweeter
WOOFER:	6.5" titanium deposit polypropylene woofer with patented Ribbed Elliptical Surround
HEIGHT:	9" / 22.85 cm (1.6" / 4cm visible height when installed)
WIDTH:	W - 9.62" / 24.44 cm (back box) W - 8.4" / 11" / 27.95 cm (outside baffle)
RECOMMENDED HOLE CUT-OUT:	Ø 9.75 / 24.8 cm
REQUIRED INSTALLATION DEPTH:	7.19" / 18.25 cm (with back box installed) 3.15" / 8 cm (without back box)
CONNECTORS:	High quality spring loaded
PACKAGING QUANTITY:	1 per box
COLORS:	White
OTHER UNIQUE FEATURES:	Weather resistant design with UV-rated enclosure. Rotatable Omniguide module. Removable back box for installations with limited mounting depth
OPTIONAL INSTALLATION BRACKET:	ICB-65